

## Features \_

- 1.28 Gpf / 4.86 Lpf
- 3 bolt tank-to-bowl connection
- Round front bowl
- High performance MagnaFlush™ flushing technology
- 3" flush valve
- Pilot operated anti-siphon fill valve
- 12" rough-in
- Front-mount, chrome-plated, metal trip lever
- 1-7/8" glazed trapway
- The Mansfield® limited lifetime warranty
- Available in white and standard colors: biscuit and bone





Model 380-387
Toilet seat not included

## Components \_\_\_\_\_

Model #	Description	Codes/Standards
380-387	Round front, two-piece toilet. Less toilet seat and supply. Specify color.	
380	Round front toilet bowl only. Less toilet seat. Specify color.	
387	Tank and cover only, with left hand, front-mount, chrome-plated, metal trip lever. Less supply. Specify color.	HIGH EFFICIENCY TOILET
387RH	Same as above, with right hand trip lever.	C V 8
*4381CTK	Round front, complete toilet kit. Includes toilet seat, tank and bowl, flange bolts, wax ring with polyethylene flange and instructions.	






## **Specifications**

Model #	Description	Codes/Standards	
380-387	Round front, (1.28 gpf / 4.86 lpf) two-piece toilet	HET CO	

Specification	Description	Specification	Description
Material	Vitreous china	Trap Diameter	1-7/8"
Water Pressure Range	20 to 80 PSI	Trap Seal	2-3/8"
MaP Rating	800 grams	Rough-in	12"
Water Usage	1.28 gpf / 4.86 lpf	Shipping Weight	Model 380 - 47 lbs., Model 387 -
Water Surface Area	8-1/2" X 9-1/2"		34 lbs., Model 4381CTK - 91 lbs.
Flush System	3" flush valve - MagnaFlush™ flushing technology	Warranty	Vitreous China - Limited Lifetime Tank Trim - Limited One Year

## **Technical Information**



See our complete line of acrylic and vitreous china bathroom fixtures, plastic tank trim and plumbing products.

These dimensions are nominal and subject to change without notice.

Fixture performance and specifications meet or exceed ASME A112.19.2-2008/CSA B45.1-08 standards, and other state and local codes.

